


I & H BEAMS, ALUMINUM ASSOCIATION



* DENOTES 1/2 COMMERCIAL TOLERANCE

i SPECIAL DIE NOTES, SEE WEBSITE FOR DETAILS

DIE #	DIMENSIONS					WEIGHT	
	W	H	P	T	R	LB/FT	KG/M
S-6872	2.000	3.000	0.250	0.188	0.375	1.877	2.793
S-23017	2.500	3.000	0.250	0.187	0.375	2.169	3.227
S-23023	3.000	4.000	0.230	0.150	0.250	2.318	3.450
S-27040	3.000	4.000	0.250	0.188	0.375	2.689	4.001
S-2296	3.000	5.000	0.218	0.250	0.437	3.083	4.588
S-3859	3.500	6.000	0.375	0.250	0.438	4.841	7.204
S-5258	4.000	4.000	0.312	0.250	0.437	4.135	6.153
S-20791	4.000	6.000	0.375	0.281	0.437	5.474	8.146
S-24405	4.500	7.000	0.380	0.230	0.300	5.820	8.661
S-20801	5.000	5.000	0.313	0.313	0.438	5.494	8.177
S-4403	5.000	5.000	0.375	0.312	0.562	6.309	9.389
S-27029	5.000	8.000	0.500	0.311	0.563	8.790	13.081
S-5411	6.000	6.000	0.375	0.312	0.625	7.637	11.365
S-24769 i	6.000	6.000	0.500	0.375	0.375	9.435	14.040
S-4851	7.250	5.500	0.312	0.250	0.312	6.876	10.233
S-17391 i	8.000	8.000	0.433	0.288	0.400	10.761	16.014
S-20745 i	8.000	8.000	0.500	0.375	0.750	13.107	19.505