

## RECTANGULAR BARS, FULL ROUND EDGES



\* DENOTES 1/2 COMMERCIAL TOLERANCE

**i** SPECIAL DIE NOTES, SEE WEBSITE FOR DETAILS

DIE #	DIMENSIONS		WEIGHT	
	W	T	LB/FT	KG/M
S-4922 <b>i</b>	0.750	0.125	0.106	0.158
S-2299	1.000	0.250	0.279	0.415
S-23745 <b>i</b>	1.125	0.125	0.162	0.241
S-24936	1.250	0.375	0.518	0.771
S-13825	1.500	0.125	0.217	0.323
S-2174	1.500	0.250	0.427	0.635
S-13822	1.750	0.156	0.316	0.471
S-2173	2.000	0.125	0.291	0.433
S-13823	2.000	0.156	0.362	0.539
S-10077	2.000	0.188	0.435	0.647
S-2269	2.000	0.250	0.574	0.854
S-2266	2.000	0.375	0.849	1.264
S-14285	2.000	0.500	1.117	1.662
S-2329	2.500	0.250	0.722	1.074
S-2175	3.000	0.250	0.869	1.293
S-2267	3.000	0.375	1.292	1.923
S-5424	3.000	0.500	1.707	2.540
S-2421	3.500	0.250	1.017	1.513
S-2887	3.688	0.125	0.540	0.804

DIE #	W	T	LB/FT	KG/M
S-2298	4.000	0.250	1.164	1.732
S-2248	4.000	0.375	1.734	2.581
S-5016	4.000	0.500	2.297	3.418
S-5423	4.000	1.000	4.466	6.646
S-13987	4.500	0.375	1.956	2.910
S-2302	5.000	0.250	1.459	2.171
S-2341	5.000	0.375	2.177	3.240
S-2172	6.000	0.250	1.754	2.610
S-2268	6.000	0.375	2.619	3.898
S-5419	6.000	0.500	3.477	5.174
S-5422	6.000	1.000	6.826	10.150
S-4952	7.000	0.250	2.050	3.050
S-12466	7.000	0.500	4.067	6.052
S-5420	8.000	0.375	3.504	5.215
S-5421	8.000	0.500	4.657	6.930
S-5693 ①	8.000	1.000	9.187	13.671
S-5829	10.000	0.375	4.390	6.532
S-6875	10.000	0.500	5.836	8.685